

DPM 845

REC'D NOV 24 1987

Informational Copy Only
Official document will be sent with first order.

MATERIAL SAFETY
DATA SHEET

3M
3M CENTER
ST. PAUL, MINNESOTA
55144-1000
612/733-1110 Duns No: 00-617-3082

DIVISION: ADHESIVES, COATINGS AND SEALERS

TRADE NAME: SCOTCH-GRIP™ 1711 Rubber and Gasket Adhesive

3M I.D. NUMBER: 62-1711-2631-1 62-1711-5530-2 62-1711-6530-1
62-1711-7530-0 62-1711-8530-9 62-1711-9530-8
62-1711-8632-4

ISSUED: June 30, 1987

SUPERCEDES: May 12, 1987

DOCUMENT: 10-2799-6

		EXPOSURE		
1. INGREDIENTS	C.A.S. NO.	PERCENT	LIMITS	
chloroprene polymer	N/A		N/D	5
magnesium resinate	N/A		N/D	5
antioxidant	N/A		N/D	5
thermoplastic resins	N/A		N/D	5
zinc oxide	N/A		N/D	5
calcium carbonate	N/A		N/D	5
TOTAL OF THE ABOVE	N/A	38.0	N/D	5
petroleum distillate*	8030-30-6	21.0	400 ppm	1
*contains 23% n-hexane	110-54-3	7.0	50 ppm	1
toluene	108-08-3	33.0	100 ppm	1
ethyl alcohol	64-17-5	1.0	1000 ppm	1

SOURCE OF EXPOSURE LIMIT DATA:

1. ACGIH Threshold Limit Values
2. Federal OSHA Permissible Exposure Limit
3. 3M Exposure Guidelines
4. Chemical Manufacturer Recommended Guidelines
5. None Established

ABBREVIATIONS:

- N/D - Not Determined
N/A - Not Applicable

2. PHYSICAL DATA

BOILING POINT:	140F
VAPOR PRESSURE:	668F 120 mm
VAPOR DENSITY:	3.0
EVAPORATION RATE (ETHER=1):	>3.5
APPEARANCE AND ODOR:	Tan, low viscosity liquid with strong solvent odor. Slight
SOLUBILITY IN WATER:	
SP. GRAVITY (WATER=1):	0.89

PERCENT VOLATILE: 61.0%
VISCOOSITY: 2000-3200 cps
pH: N/D

Informational Copy Only
Official document will be sent with first order.

MSDS: SCOTCH-GRIP(TM) 1711 Rubber and Gasket Adhesive
June 30, 1987

PAGE 3

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (C.C. Petro. Dist.): -14F
FLAMMABLE LIMITS - LEL: 1.0 UEL: 8.0

EXTINGUISHING MEDIA:

CO₂, foam, dry chemical

SPECIAL FIRE FIGHTING PROCEDURES:

Fire fighters should be equipped with self-contained breathing apparatus when fighting fires involving this material.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Extremely Flammable. Overheated, closed containers adjacent to fire could explode due to pressure buildup.

4. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY - MATERIALS TO AVOID:

Oxidizers

HAZARDOUS POLYMERIZATION - MAY NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition or burning may produce CO, CO₂, HCl and other chlorinated decomposition products.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Observe precautions in all sections. Extinguish all ignition sources. Collect spilled material, cleanup residue and store in closed metal container (U.S. Dept. of Transportation approved if waste will be shipped).

RECOMMENDED DISPOSAL:

Commercial incineration with destruction and removal efficiency greater than 99.99% or reclamation is preferred. If incinerated, more than 99% of the hydrogen chloride in exhaust gas should be removed. Otherwise, dispose in accordance with local and current U.S. Environmental Protection Agency regulations.

U.S. EPA Hazardous Waste Number: D001 (Ignitable).

ENVIRONMENTAL DATA:

N/D

Informational Copy Only

Official document will be sent with first order.

MSDS: SCOTCH-GRIP(TM) 1711 Rubber and Gasket Adhesive
June 30, 1987

PAGE 4

=====

6. SUGGESTED FIRST AID

=====

EYE CONTACT:

Flush eyes immediately with plenty of water for at least 10 minutes.
Call a physician.

SKIN CONTACT:

Wash area with soap and water.

INHALATION:

Move affected person to fresh air at once. Restore or support
breathing as necessary. If breathing difficulties persist, call a
physician.

IF SWALLOWED:

Do not induce vomiting. Give victim two glasses of milk or water to
drink and call a physician immediately. If spontaneous vomiting
should occur, lower the victim's head between the knees to prevent
aspiration into the lungs. Do not give liquids to an unconscious
person.

=====

7. PRECAUTIONARY INFORMATION

=====

Keep away from heat, sparks and flame. Use only in areas adequately
ventilated with enough air movement to remove vapors and prevent
vapor buildup. The vapors released by this product can be easily
ignited. Avoid contact with eyes and skin. Avoid prolonged
breathing of vapors. Keep container closed when not in use. Keep
out of the reach of children.

NOTE: Utilize personal protective equipment when handling this
product, i.e. impervious gloves and chemical goggles or safety
glasses depending on exposure conditions.

Informational Copy Only

Official document will be sent with first order.

MSDS: SCOTCH-GRIP(TM) 1711 Rubber and Gasket Adhesive
June 30, 1987

PAGE 5

=====

8. HEALTH HAZARD DATA

=====

EYE CONTACT: Liquid irritating to eyes; Can cause tearing, redness

and blurred vision.

SKIN CONTACT: Acute exposure is mildly irritating. Prolonged or repeated contact will produce defatting and resultant dermatitis.

INHALATION: Inhalation of vapors at concentrations exceeding the established exposure limits may cause respiratory system irritation. Symptoms of overexposure include drowsiness, light-headedness, dizziness, nausea and headache. Repeated or extreme overexposure to toluene vapors or n-hexane may cause nervous system damage.

INGESTION: Swallowing may cause gastrointestinal irritation, nausea, diarrhea and nervous system impairment. Solvent aspiration into the lung as a result of vomiting may cause lung damage.

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this Data Sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.

Los Angeles Branch Sales Center/3M

8023 South Garfield Avenue
PO Box 54019
Los Angeles, California 90054
213/728 6300



FAX COMMUNICATION

FAX # 213-593-9838

TO: DAVID SICILIANO
MCDONNELL DOUGLAS

FROM: Sherri Elkaim
3M - LOS ANGELES SALES CENTER (01-020)

REPLY FAX # - 213-727-2136
213-726-6585 (GROUP I, II, III)
(TRIMINET 635-6585)

4

DOCUMENTS TO FOLLOW

FAKED BY: JM DATE/TIME: 11/24 9:25